

# ICM870-9A/16A

**Soft Start** 



**APPLICATIONS:** 

APPLIANCE | ELECTRICAL | HVAC/R | MARINE | POOL & SPA | RV



#### **OVERVIEW**

The **ICM870** is intended for marine, recreational vehicle (RV), residential and commercial applications. The **ICM870** integrates compressor or motor in-rush current over startup time, thus reducing peak current demand on a power supply source, such as a generator.

The **ICM870** will monitor system health including voltage, current, compressor startup and self integrity. Upon a fault condition, the **ICM870** will halt operation and initiate a 4-minute anti-short cycle routine while providing diagnostic fault information by means of an LED indicator.

### **FEATURES**

- ▼ Reduces in-rush current/draw necessary at startup by up to 70%
- Prolongs the life of A/C by reducing excessive torque, wear and tear
- ▼ Built-in dynamic start delay
- Reduces loud noises, light flickering, and breaker trips
- ▼ Built-in self-learning algorithm
- √ Over-current protection
- √ Over/under voltage monitoring
- ▼ Built-in start capacitor
- **∨** LED fault indicators
- Ultrasonically sealed tamper-proof enclosure
- Installation hardware is included

## **SPECIFICATIONS**

- Inputs: L1 & L2
- Nominal voltage: 120 VAC, 240 VAC
- Over voltage limits: 120 VAC nominal = 140 VAC, 240 VAC nominal = 264 VAC
- Under voltage limits: 120 VAC nominal = 95 VAC, 240 VAC nominal =195 VAC
- Outputs: Compressor
- Current: Maximum nominal = 9A and 16A
- Over current limits:
  - ICM870-9A = 11.25A
  - ICM870-16A = 20A
- Operating temperature: -40°F to 131°F (-40°C to 55°C)
- Storage temperature: -40°F to 149°F (-40°C to 65°C)
- **Humidity:** 0-95% non-condensing
- Enclosure: IP65/Type 4X
- **Dimensions:** 7.94" x 4.20" x 2.10"

#### **REPLACES**

The **ICM870-9A** and **ICM870-16A** models replace the amperage-corresponding models from the following manufacturers:

**Dometic** (SmartStart)

**Hyper Engineering** (Sure-Start)

Micro-Air (EasyStart)

Network RV (SoftStartRV)

Carlo Gavazzi (SmoothStarter)

Content and specifications on sell sheets subject to change without notice.



