


## ELIMINATOR® AC

### USA Made Economy Vacuum Pump

- 1/2 HP 1725 RPM motor
- Available in 3, 4 and 6 CFM
- Easy access 1/4" or 3/8" intake tee
- 25 micron vacuum rating
- All-metal construction with burnished cover, brass fittings and stainless steel valving
- Ergonomic 1/2" break-resistant exhaust handle
- Large, easy-to-see oil level sight glass with easy access oil fill
- Tethered safety cap to prevent oil spills
- 100% field repairable; see page 76 for repair parts
- Available in 115v or dual voltage motor with switch (115v/230v)
- Removable, interchangeable power cord on dual voltage motors
- 2 year OTC warranty
- Made in the USA 



DV-6E

### Spark-Proof Pump

Spark-proof, dual voltage motor with switch and removable, interchangeable power cord for use on Class A1, A2L, A2 and A3 refrigeration systems, **DV-6E-250SP**

### International Dual Voltage Pump

ELIMINATOR -250 and -250SP Series models feature a dual voltage motor with switch and removable, interchangeable power cord. Specify US, EU, UK, AU or BR plug type.



DV-6E-250SP  
Spark-Proof

ELIMINATOR PUMPS				
	DV-3E	DV-4E	DV-6E	
<b>CFM</b>	3 CFM (85 l/m)	4 CFM (113 l/m)	6 CFM (170 l/m)	
<b>MOTOR</b>	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	1/2 HP, 1725 RPM	
<b>VOLTAGE</b>	115v/60Hz	115v/60Hz	115v/60Hz	
<b>INTAKE PORT</b>	1/4" x 3/8"	1/4" x 3/8"	1/4" x 3/8"	
<b>OIL CAPACITY</b>	28oz (828cc)	25oz (739cc)	25oz (739cc)	
<b>SHIPPING DIMS</b>	17-5/8" x 9-1/8" x 14"	17-5/8" x 9-1/8" x 14"	17-5/8" x 9-1/8" x 14"	
<b>WEIGHT</b>	29lbs (13.2kg)	30lbs (13.6kg)	30lbs (13.6kg)	
ELIMINATOR DUAL VOLTAGE				
	DV-3E-250	DV-4E-250	DV-6E-250	DV-6E-250SP
<b>MOTOR</b>	1/2 HP, 1725/1425 RPM	1/2 HP, 1725/1425 RPM	1/2 HP, 1725/1425 RPM	1/2 HP, 1725/1425 RPM
<b>VOLTAGE</b>	115v/60Hz, 230v/50Hz	115v/60Hz, 230v/50Hz	115v/60Hz, 230v/50Hz	115v/60Hz, 230v/50Hz
<b>PLUG</b>	US 220v	US 220v	US 220v	US 220v
<b>PLUG OPTIONS*</b>	US/EU/UK/AU/BR	US/EU/UK/AU/BR	US/EU/UK/AU/BR	US/EU/UK/AU/BR