



CLV Series

KOBRA® Gasket Seal Quarter-Turn Ball Valve Hose with 6" Whip End

- 800 psi working; 4000 psi burst
- Meets non-venting requirements by trapping refrigerant with ball valve
- **CLV6:** 6" Ball valve with whip end
- **CLP:** 6" Whip end only
- Made in the USA



| CLV SERIES KOBRA® 1/4" X 1/4" W/BALL VALVE WHIP END (psi 800/4000) | | | | | |
|--|---|--------------------|---------------------|------------------|---------------------------|
| LENGTH | BLUE | YELLOW | RED | B/Y/R 3 PACK | B/Y/R BLACK (3/8") 4 PACK |
| 36" (91cm) | CLV-36B | CLV-36Y | CLV-36R | CCLV-36 | CCLV4-36 |
| 48" (122cm) | CLV-48B | CLV-48Y | CLV-48R | CCLV-48 | CCLV4-48 |
| 60" (152cm) | CLV-60B | CLV-60Y | CLV-60R | CCLV-60 | CCLV4-60 |
| 72" (182cm) | CLV-72B | CLV-72Y | CLV-72R | CCLV-72 | CCLV4-72 |
| CLV SERIES W/BALL VALVE WHIP END ONLY (psi 800/4000) | | | | | |
| 1/4" x 6" | CLV-6B | CLV-6Y | CLV-6R | CCLV-6 | CLV-6BL |
| 3/8" x 6" | | CLV6-6Y | | | CLV6-6BL |
| CLP SERIES KOBRA® 1/4" X 1/4" HOSE WHIP END ONLY (psi 800/4000) | | | | | |
| 6" (15cm) | CLP-6B | CLP-6Y | CLP-6R | | |
| CLV6 AND CL6 SERIES KOBRA® 3/8" X 3/8" CHARGING HOSE (psi 600/3000) | | | | | |
| LENGTH | BLACK | BLACK W/BALL VALVE | YELLOW | | |
| 36" (91cm) | CL6-36 | CLV6-36 | CL6-36Y | | |
| 48" (122cm) | CL6-48 | CLV6-48 | CL6-48Y | | |
| 60" (152cm) | CL6-60 | CLV6-60 | CL6-60Y | | |
| 72" (182cm) | CL6-72 | CLV6-72 | CL6-72Y | | |
| CLV5 AND CCLV5 SERIES KOBRA® W/BALL VALVE WHIP END 1/4" X 5/16" (psi 800/4000) | | | | | |
| LENGTH | BLUE/RED: 1/4" x 5/16" YELLOW: 1/4" x 1/4" 3 PACK | BLUE 1/4" x 5/16" | YELLOW 1/4" x 5/16" | RED 1/4" x 5/16" | |
| 36" (91cm) | CCLV5-36 | | | | |
| 60" (152cm) | CCLV5-60 | CLV5-60B | CLV5-60Y | CLV5-60R | |
| 72" (182cm) | CCLV5-72 | | | | |

Heavy-Duty Series

1/4", 3/8" and 1/2" Heavy-Duty Black Charging Hose

- **1/4":** 800 psi working; 4000 psi burst
- **3/8":** 800 psi working; 4000 psi burst
- **1/2":** 640 psi working; 3200 psi burst
- Heavy-duty charging hose reduces permeation
- Straight fittings by straight fittings
- Made in the USA



| HEAVY-DUTY BLACK CHARGING (psi 1/4", 3/8" 800/4000, 1/2" 640/3200) | | | |
|--|-------------------------------|-------------------------------|---------------------|
| LENGTH | BLACK (1/4" X 1/4") | BLACK (3/8" X 3/8") | BLACK (1/2" X 1/2") |
| 36" (91cm) | CL4HD-36 | CL6HD-36 | CL2HD-36 |
| 48" (122cm) | CL4HD-48 | CL6HD-48 | CL2HD-48 |
| 60" (152cm) | CL4HD-60 | CL6HD-60 | CL2HD-60 |
| 72" (182cm) | CL4HD-72 | CL6HD-72 | CL2HD-72 |
| HEAVY-DUTY BLACK EVACUATION/CHARGING HOSE (psi 800/4000) | | | |
| LENGTH | BLACK (3/8") | BLACK (1/2") | |
| 60" (152cm) | CL64-60 (1/4" x 3/8" fitting) | CL84-60 (1/4" x 1/2" fitting) | |

Standard Series

1/4" Standard Charging Hose

- 750 psi working; 3000 psi burst
- Ideal for use with all standard refrigerants (except high pressure)
- Permeation can be detected and will vary with refrigerant type and time of exposure
- Made in the USA



| STANDARD 1/4" X 1/4" CHARGING HOSE (psi 750/3000) | | | | |
|---|--------|--------|--------|--------------|
| LENGTH | BLUE | YELLOW | RED | B/Y/R 3 PACK |
| 36" (91cm) | CL-36B | CL-36Y | CL-36R | CCL-36 |
| 48" (122cm) | CL-48B | CL-48Y | CL-48R | CCL-48 |
| 60" (152cm) | CL-60B | CL-60Y | CL-60R | CCL-60 |
| 72" (182cm) | CL-72B | CL-72Y | CL-72R | CCL-72 |