



NOARK DP Contactors provide high performance with both flexibility and reliability. They are designed to match numerous applications.

# NOARK

## CONTACTORS



### APPLICATIONS INCLUDE:

- HVACR
- Resistive heating
- Refrigeration equipment
- Motors
- Welding
- Pumps
- Power supplies
- Food service equipment
- Compressors
- Business machines

### CERTIFICATIONS:

- UL 508 Recognized, File No. E353866
- CSA Certified, C22.2 No. 265900
- IEC/EN 60947 Compliant
- CE Approved
- Compliance to ARI-780 HVAC Standards
- RoHS Compliant



*All Contactors with Lugs*

Exclusive  Distributor

# DEFINITE PURPOSE CONTACTORS

# NOARK

Part Number	Pole Count	Voltage	Amperage	Case Qty
N4143	1 with shunt	24 V	30 A	64
N4164	1 with shunt	24 V	40 A	64
N4101	2	24 V	20 A	64
N4104	2	24 V	25 A	64
N4107	2	24 V	30 A	64
N4161	2	24 V	40 A	64
N4102	2	120 V	20 A	64
N4105	2	120 V	25 A	64
N4108	2	120 V	30 A	64
N4162	2	120 V	40 A	64
N4106	2	208/240 V	25 A	64
N4109	2	208/240 V	30 A	64
N4163	2	208/240 V	40 A	64
N4113	3	24 V	30 A	54
N4116	3	24 V	40 A	54
N4128	3	24 V	50 A	27
N4131	3	24 V	60 A	27
N4114	3	120 V	30 A	54
N4117	3	120 V	40 A	54
N4129	3	120 V	50 A	27
N4132	3	120 V	60 A	27
N4135	3	120 V	75 A	12
N4115	3	208/240 V	30 A	54
N4118	3	208/240 V	40 A	54
N4130	3	240 V	50 A	27
N4133	3	240 V	60 A	27
N4136	3	240 V	75 A	12

## AVAILABLE AS:

- Rated current from 20 - 75 A
- 1, 2, and 3 pole configurations for HVACR
- Enclosed coil standard for all 3 pole frame sizes
- Industry standard mounting plate provides easily accessible mounting holes
- Lug connections with quick connect spades
- Coil is Class B 266°F (130°C) insulation system with a wide range of voltages
- 50/60Hz ratings for 2 and 3 pole configurations
- Double E magnet assembly provides optimal performance with reduced power consumption
- 1NO+1NC auxiliary contact block with 600 V rating is an available option on 3 pole contactors
- Noark Auxiliary contactors: AXFC11, AXFC11Q
- Base assembly is made from high arc-resistant polyester

*All Contactors with Lugs*

## NOARK – COMPARISON CHART

Feature	Noark	Jard	Mars (Blue Box)	Mars 780	Packard	Titan Max
Box Lugs	✓	✓	✓	✓	✓	✓
Enclosed Body	✓		✓	✓	✓	✓
Copper & Brass Terminals	✓		✓	✓	✓	✓
Silver Cadmium Contacts	✓		✓	✓	✓	✓
ARI 780/790	✓		✓	✓		✓
Aux Switches Available	✓	✓	✓	✓	✓	✓
1,000,000 Cycle Mech. Life	✓		✓	✓		✓
Polyester Base Assembly	✓					
5 Year Warranty	✓					

*Trust the* **(G)**