

## Digital Multimeters

### LT17A

#### The Biggest Bang for Your Buck

The LT series cover most parameters and ranges technicians need for HVACR applications. And to further expand testing capabilities, the leads connect directly to any Fieldpiece accessory head.



- Continuity indicator
- Type K thermocouple
- Bright, blue backlight
- Low ohm ranges
- Both mA and  $\mu$ A for testing flame rectifier diodes
- MIN/MAX function
- Probe storage
- Magnetic hanger and tilt stand

#### Included

- Deluxe silicone test leads – ADLS2
- Short alligator lead extensions – ASA2
- 400A amp clamp accessory – ACH4
- Type K thermocouple – ATB1
- Nylon case – ANC5



## Dual Alligator Clips

### ADA2

- Red and black vinyl insulated cables with small alligator clips on the ends. Each shorting cable is 3.5 feet long



## Current Clamp Head

### ACH4

- Measures AC Amps from 1A to 400A
- Accuracy:
  - 1A-20A AC:  $\pm(1.5\% \text{ rdg} + 0.2A)$
  - 20A-100A AC:  $\pm(2.5\% \text{ rdg} + 0.3A)$
  - 100A-400A AC:  $\pm(3.5\% \text{ rdg} + 0.5A)$
- .91" (23mm) maximum conductor diameter



## Electronic Handle for Accessory Heads

### EHD1

Converts any Fieldpiece Accessory Head into a standalone instrument.

- MIN/MAX button
- Use with any Fieldpiece accessory head
- Hold button



## Silicone Test Leads

### ASLS2

- High copper strands, silicone insulated test leads
- Basket style strain relief



## Deluxe Silicone Test Leads

### ADLS2

- Same as the ASLS2 with the addition of removable probe tips for connection to accessory heads



## Deluxe Test Lead Kit

### ADK7

- Silicone test leads, removable probe tips and alligator clips for grounding
- Includes moxex tips

