

ELECTRICAL | ELECTRICAL ACCESSORIES

ACCESSORIES CONT'D

5-Outlet GFCI Shock Buster

GFCI Protected
 Plug into any 3-prong dual outlet
 Converts electrical outlet into a safety outlet
 Ideal for family TV rooms, dens, dormitory rooms, garage workshops and rec-rooms
 Protects from damaged electrical cords and hazardous electrical leakage levels
 Quick power shut off to avoid electrocution
 Built-in sensing device to detect leakage currents as low as 4mA
 15 Amp 120 Volt



89009



CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
89009	5-Outlet GFCI Shock Buster	EA	60

Hose Clamps

Partial stainless, worm drive, adjustable. 300 series stainless steel 1/2" band with plated 5/16" slotted hex head screw and housing, except the B-4H which has a 5/16" band and 1/4" nut. Recommended for most applications. 100% interlock construction features one-piece housing which directly locks into band. Spot weld free design.



B-4H

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
B-4H	No. 4, 7/32" – 5/8" dia., 3/16" – 5/16" hose I.D.	EA	10
B-6H	No. 6, 7/16" – 25/32" dia., 1/4" – 3/8" hose I.D.	EA	10
B-8H	No. 8, 1/2" – 29/32" dia., 5/16" – 1/2" hose I.D.	EA	10
B-10H	No. 10, 9/16" – 1-1/16" dia., 3/8" – 5/8" hose I.D.	EA	10
B-12H	No. 12, 11/16" – 1-1/4" dia., 5/8" – 3/4" hose I.D.	EA	10
B-16H	No. 16, 13/16" – 1-1/2" dia., 3/4" – 1" hose I.D.	EA	10
B-20H	No. 20, 13/16" – 1-3/4" dia., 1" – 1-1/4" hose I.D.	EA	10
B-24H	No. 24, 1-1/16" – 2" dia., 1-1/4" – 1-1/2" hose I.D.	EA	10
B-28H	No. 28, 1-5/16" – 2-1/4" dia., 1-1/4" – 1-3/4" hose I.D.	EA	10
B-32H	No. 32, 1-9/16" – 2-1/2" dia., 1-1/2" – 2" hose I.D.	EA	10
B-36H	No. 36, 1-13/16" – 2-3/4" dia., 1-3/4" – 2-1/4" hose I.D.	EA	10
B-48H	No. 48, 2-9/16" – 3-1/2" dia., 1-3/4" – 2-1/4" hose I.D.	EA	10
B-72H	No. 72, 1-7/8" – 5" dia., 1-3/4" – 2-1/4" hose I.D.	EA	10

Electrical Toggle Switches

Side wire design with automatic grounding and large binding head terminal screws for fast wiring. Lubricated cam provides smooth lever action. U.L. Listed. C.S.A. Certified. Verified to Federal Spec. WS896E



620-601

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
620-600	20A-1 HP 120V, Single Pole, Brown	EA	10
620-601	20A-1 HP 120V, Single Pole, Ivory	EA	10
625-CS120W	20A-1HP 120V Single Pole, White	EA	10
625-1301W	15A-1/2HP 120V Single Pole, White	EA	10
620-604	15A-1/2 HP 120V, Single Pole, Brown	EA	10
620-605	15A-1/2 HP 120V, Single Pole, Ivory	EA	10

U.L. Listed. C.S.A. Certified. Verified to Federal Spec. WS896E.

Electrical Duplex Receptacles

Automatic grounding for fast installation. Heavy duty mounting strap for additional assembly strength. Copper alloy power/ground contacts for optimum continuity. Side wire design with large binding head terminal screws for fast wiring. U.L. Listed. C.S.A. Certified (NEMA 5 15 Type).



620-701



620-700



625-CR15W



620-704

CATALOG NO.	DESCRIPTION	UOM	ORDER MULTIPLE
620-700	15A, 125V, Brown	EA	10
620-701	15A, 125V, Ivory	EA	10
625-CR15W	15A 125V, White	EA	10
620-702	20A, 125V, Brown	EA	10
620-703	20A, 125V, Ivory	EA	10
625-CR20W	20A 125V, White	EA	10
620-704	15A, 125V, Brown – Residential	EA	10
620-705	15A, 125V, Ivory – Residential	EA	10
625-270W	15A 125V, White – Residential	EA	10

U.L. Listed. C.S.A. Certified (NEMA 5-15 Type).