

DIAGONAL-CUTTING PLIERS


Angled-Head Diagonal-Cutting Pliers

Includes core High-Leverage Diagonal-Cutting features plus:

- Angled head design for easy work in confined spaces
- Glow-in-the-Dark grips are easily spotted in dark or low lit areas (Cat. No. D248-8-GLW)



D2000-49



13°

ANGLED HEAD PROFILE

HANDLE FINISH



Plastic-Dipped

GLOW-IN-THE-DARK Plastic-Dipped

JOURNEYMAN™ Dual-Material

INS INSULATED 2-Layer Protection

EINS INSULATED 3-Layer Protection

1000 V

1000 V

Cat. No.	Jaw Length	Jaw Width	Jaw Thickness	Cutting Knives	Handle Color	Handle Finish	Overall Length
D238-8	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Semi-Flush	Red	Plastic-Dipped	8.05" (20.45 cm)
D248-8	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Red	Plastic-Dipped	8.05" (20.45 cm)
D248-8-INS	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Orange	2-Layer Insulation	8.24" (20.93 cm)
D248-8-GLW	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Glow-in-the-Dark	Plastic-Dipped	8.06" (20.47 cm)
J248-8	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Red/Black	Journeyman™ Dual-Material	8.16" (20.73 cm)

With heavy-duty cutting knives designed to cut ACSR, screws, nails and most hardened wire

200048EINS	0.813" (2.07 cm)	1.25" (3.18 cm)	0.48" (1.22 cm)	Standard	Orange/Gray	3-Layer Insulation	8.15" (20.70 cm)
D2000-48	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Blue	Plastic-Dipped	8.05" (20.45 cm)
D2000-48-INS	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Orange	2-Layer Insulation	8.24" (20.93 cm)
D2000-49	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Yellow	Plastic-Dipped	9" (22.86 cm)
J2000-48	0.813" (2.07 cm)	1.25" (3.18 cm)	0.46" (1.17 cm)	Standard	Light Blue/Black	Journeyman™ Dual-Material	8.04" (20.42 cm)

Ironworker's Diagonal-Cutting Pliers

Includes core High-Leverage Diagonal-Cutting features plus:

- Angled head design for easy working in confined spaces
- Hooked-handle for improved grip



13°

ANGLED HEAD PROFILE



SPLIT TETHER RING D248-9STT



D248-9STT

Cat. No.	Jaw Length	Jaw Width	Jaw Thickness	Cutting Knives	Handle Color	Handle Finish	Overall Length
D248-9ST	0.813" (2.07 cm)	1.188" (3.02 cm)	0.46" (1.17 cm)	Standard	Red	Plastic-Dipped	9.13" (23.19 cm)
D248-9STT	0.813" (2.07 cm)	1.188" (3.02 cm)	0.46" (1.17 cm)	Standard	Red	Plastic-Dipped	9.13" (23.19 cm)

Standard Diagonal-Cutting Pliers

- Tapered nose for easy working in confined areas and close tip cutting
- Trims plastic or printed circuit boards (Cat. D210-6C)
- Heavier design for all-purpose use (Cat. Nos. D220-7, D220-7-INS, D252-6, and D252-6SW)



D245-5



D220-7

16 AWG SOLID WIRE STRIPPING HEAD D240-6

HANDLE FINISH



Plastic-Dipped

INS INSULATED 2-Layer Protection

1000 V

Cat. No.	Jaw Length	Jaw Width	Jaw Thickness	Cutting Knives	Handle Color	Handle Finish	Overall Length
D202-6	0.798" (2.03 cm)	1.03" (2.62 cm)	0.43" (1.09 cm)	Standard	Red	Plastic-Dipped	6.16" (15.65 cm)
D202-6C	0.798" (2.03 cm)	1.03" (2.62 cm)	0.43" (1.09 cm)	Standard	Red	Plastic-Dipped	6.16" (15.65 cm)
D210-6C	0.798" (2.03 cm)	1.03" (2.62 cm)	0.43" (1.09 cm)	Semi-Flush	Red	Plastic-Dipped	6.16" (15.65 cm)
D220-7	1" (2.54 cm)	0.969" (2.5 cm)	0.5" (1.27 cm)	Standard	Red	Plastic-Dipped	7.65" (19.43 cm)
D220-7-INS	1" (2.54 cm)	0.969" (2.5 cm)	0.5" (1.27 cm)	Standard	Orange	2-Layer Insulation	7.67" (19.48 cm)
D245-5	0.696" (1.77 cm)	0.563" (1.4 cm)	0.35" (0.89 cm)	Standard	Red	Plastic-Dipped	5.1" (12.95 cm)
D240-6	0.831" (2.11 cm)	0.74" (1.88 cm)	0.428" (1.09 cm)	Standard	Red	Plastic-Dipped	6.16" (15.65 cm)
D252-6	0.696" (1.77 cm)	0.75" (1.91 cm)	0.813" (2.07 cm)	Standard	Red	Plastic-Dipped	6.15" (15.62 cm)

Bell-System Type "W" & "V" Notches — for quick insulation slitting

D252-6SW	0.696" (1.77 cm)	0.75" (1.91 cm)	0.813" (2.07 cm)	Standard	Red	Plastic-Dipped	6.15" (15.62 cm)
----------	------------------	-----------------	------------------	----------	-----	----------------	------------------

Telephone Type D-6 "V" Notches — for quick insulation slitting and includes .030" and .045" stripping holes

72192	0.813" (2.07 cm)	0.75" (1.91 cm)	0.813" (2.07 cm)	Standard	Red	Plastic-Dipped	6.125" (15.56 cm)
-------	------------------	-----------------	------------------	----------	-----	----------------	-------------------



Pliers
Strippers, Cutters, and Crimpers
Drivers and Wrenches
Conduit Tools and Measurement
Tool Kits
Safety, PPE and Comfort
Job Site Accessories
Tool Storage
Voice/Data Video
Test and Measurement
Power Tools and Accessories
Lifting, Pulling and Structural