and Structural



## **Digital Pocket Thermometers**

- User selectable Fahrenheit and Celsius temperature measurements
- Backlit display for easy viewing in low light
- Max/Min, Hold and Average functions
- Auto-power off after 15 minutes conserves battery life
- FDA GRAS compliant for food usage
- Lightweight, compact tool with pocket clip provides easy storage and quick access
- Cat. No. ET05 has a range of -40° to 482° F (-40° to 250° C);
  Cat. No. ET10 has a range of -40° to 572° F (-40° to 300° C)
- Cat. No. ET10 features a magnet inside base of probe to easily attach to vents for hand-free IAQ (indoor air quality) measurements



ET05





Cat. No.	Batteries	Overall Length	Overall Height	Overall Width
ET05	2 x LR44	6.50" (16.5 cm)	0.94" (2.4 cm)	1.08" (2.7 cm)
ET10 🔼	2 x LR44	6.50" (16.5 cm)	0.97" (2.5 cm)	1.25" (3.2 cm)



## **Dual Infrared and Probe Thermometer**

- Pocket tester measures temperature from -40° to 572° F (-40° to 300°C)
- Accurately measure surface temperature with infrared thermometer (DS ratio 8:1)
- Measure inside air vents and duct temperatures with temperature probe with hanging hook
- Quickly calculates differential temperature (T1-T2) for both IR and probe temperatures
- Backlit display with Hold, Max/Min, APO, and Low Battery functions
- Includes: pouch, instruction manual and 2 x AAA batteries





C € EK

Cat. No.	Batteries	Overall Length	Overall Height	Overall Width
IR07	2 x AAA	5.82" (14.8 cm)	0.95" (2.4 cm)	1.67" (4.2 cm)

